


Machine Learning: Decision Trees in AIMA, WEKA and SCIKIT-LEARN



UCI



Machine Learning Repository

Center for Machine Learning and Intelligent Systems

View ALL Data Sets

Welcome to the UC Irvine Machine Learning Repository!

• Est. 1987!
• 370 data sets

We currently maintain 233 data sets as a service to the machine learning community. You may view all data sets through our searchable interface. Our old web site is still available, but is still in beta. If you wish to donate a data set, please consult our donation policy. For any other questions, feel free to contact the Repository librarians. We have also set up a mirror site for the Repository.

Supported By:




In Collaboration With:



Latest News:

- 2010-03-01: Note from donor regarding Netflix data
2009-10-16: Two new data sets have been added.
2009-09-14: Several data sets have been added.
2008-07-23: Repository mirror has been set up.
2008-03-24: New data sets have been added!
2007-06-25: Two new data sets have been added: UJI Pen Characters, MAGIC Gamma Telescope
2007-04-13: Research papers that cite the repository have been associated to specific data sets.

Featured Data Set: Yeast



Task: Classification
Data Type: Multivariate
Attributes: 8
Instances: 1484

Predicting the Cellular Localization Sites of Proteins

Newest Data Sets:

- 2012-10-21: UCI QtyT40I10D100K
2012-10-19: UCI Legal Case Reports
2012-09-29: UCI seeds
2012-08-30: UCI Individual household electric power consumption
2012-08-15: UCI Northix
2012-08-06: UCI PAMAP2 Physical Activity Monitoring
2012-08-04: UCI Restaurant & consumer data
2012-08-03: UCI CNAE-9

Most Popular Data Sets (hits since 2007):

- 386214: Iris
272233: Adult
237503: Wine
195947: Breast Cancer Wisconsin (Diagnostic)
182423: Car Evaluation
151635: Abalone
135419: Poker Hand
113024: Forest Fires



A A

http://archive.ics.uci.edu/ml/datasets/Zoo

Google



[About](#) [Citation Policy](#) [Donate a Data Set](#) [Contact](#)

Search

Repository Web



Machine Learning Repository

[Center for Machine Learning and Intelligent Systems](#)

[View ALL Data Sets](#)

Zoo Data Set

Download: [Data Folder](#), [Data Set Description](#)



Abstract: Artificial, 7 classes of animals

<http://archive.ics.uci.edu/ml/datasets/Zoo>

Data Set Characteristics:	Multivariate	Number of Instances:	101	Area:	Life
Attribute Characteristics:	Categorical, Integer	Number of Attributes:	17	Date Donated	1990-05-15
Associated Tasks:	Classification	Missing Values?	No	Number of Web Hits:	18038

- 1) animal name: string
- 2) hair: Boolean
- 3) feathers: Boolean
- 4) eggs: Boolean
- 5) milk: Boolean
- 6) airborne: Boolean
- 7) aquatic: Boolean
- 8) predator: Boolean
- 9) toothed: Boolean
- 10) backbone: Boolean
- 11) breathes: Boolean
- 12) venomous: Boolean
- 13) fins: Boolean
- 14) legs: {0,2,4,5,6,8}
- 15) tail: Boolean
- 16) domestic: Boolean
- 17) catsize: Boolean
- 18) type: {mammal, fish, bird, shellfish, insect, reptile, amphibian}

Zoo training data

category
label



101 Instances

```
aardvark,1,0,0,1,0,0,1,1,1,1,0,0,4,0,0,1,mammal
antelope,1,0,0,1,0,0,0,1,1,1,0,0,4,1,0,1,mammal
bass,0,0,1,0,0,1,1,1,1,0,0,1,0,1,0,0,fish
bear,1,0,0,1,0,0,1,1,1,1,0,0,4,0,0,1,mammal
boar,1,0,0,1,0,0,1,1,1,1,0,0,4,1,0,1,mammal
buffalo,1,0,0,1,0,0,0,1,1,1,0,0,4,1,0,1,mammal
calf,1,0,0,1,0,0,0,1,1,1,0,0,4,1,1,1,mammal
carp,0,0,1,0,0,1,0,1,1,0,0,1,0,1,1,0,fish
catfish,0,0,1,0,0,1,1,1,1,0,0,1,0,1,0,0,fish
cavy,1,0,0,1,0,0,0,1,1,1,0,0,4,0,1,0,mammal
cheetah,1,0,0,1,0,0,1,1,1,1,0,0,4,1,0,1,mammal
chicken,0,1,1,0,1,0,0,0,1,1,0,0,2,1,1,0,bird
chub,0,0,1,0,0,1,1,1,1,0,0,1,0,1,0,0,fish
clam,0,0,1,0,0,0,1,0,0,0,0,0,0,0,0,0,shellfish
crab,0,0,1,0,0,1,1,0,0,0,0,0,4,0,0,0,shellfish
...
```

Zoo example

```
aima-python> python
```

```
>>> from learning import *
```

```
>>> zoo
```

```
<DataSet(zoo): 101 examples, 18 attributes>
```

```
>>> dt = DecisionTreeLearner()
```

```
>>> dt.train(zoo)
```

```
>>> dt.predict(['shark',0,0,1,0,0,1,1,1,1,0,0,1,0,1,0,0]) #eggs=1  
'fish'
```

```
>>> dt.predict(['shark',0,0,0,0,0,1,1,1,1,0,0,1,0,1,0,0]) #eggs=0  
'mammal'
```

Zoo example

```
>> dt.dt
```

```
DecisionTree(13, 'legs', {0: DecisionTree(12, 'fins', {0:  
DecisionTree(8, 'toothed', {0: 'shellfish', 1: 'reptile'}), 1:  
DecisionTree(3, 'eggs', {0: 'mammal', 1: 'fish'})}), 2:  
DecisionTree(1, 'hair', {0: 'bird', 1: 'mammal'}), 4:  
DecisionTree(1, 'hair', {0: DecisionTree(6, 'aquatic', {0:  
'reptile', 1: DecisionTree(8, 'toothed', {0: 'shellfish', 1:  
'amphibian'})}), 1: 'mammal'}), 5: 'shellfish', 6:  
DecisionTree(6, 'aquatic', {0: 'insect', 1: 'shellfish'}), 8:  
'shellfish'})
```

Zoo example

```
>>> dt.dt.display()
```

```
Test legs
```

```
legs = 0 ==> Test fins
```

```
    fins = 0 ==> Test toothed
```

```
        toothed = 0 ==> RESULT = shellfish
```

```
        toothed = 1 ==> RESULT = reptile
```

```
    fins = 1 ==> Test eggs
```

```
        eggs = 0 ==> RESULT = mammal
```

```
        eggs = 1 ==> RESULT = fish
```

```
legs = 2 ==> Test hair
```

```
    hair = 0 ==> RESULT = bird
```

```
    hair = 1 ==> RESULT = mammal
```

```
legs = 4 ==> Test hair
```

```
    hair = 0 ==> Test aquatic
```

```
        aquatic = 0 ==> RESULT = reptile
```

```
        aquatic = 1 ==> Test toothed
```

```
            toothed = 0 ==> RESULT = shellfish
```

```
            toothed = 1 ==> RESULT = amphibian
```

```
    hair = 1 ==> RESULT = mammal
```


```
legs = 5 ==> RESULT = shellfish
```

```
legs = 6 ==> Test aquatic
```

```
    aquatic = 0 ==> RESULT = insect
```

```
    aquatic = 1 ==> RESULT = shellfish
```

```
legs = 8 ==> RESULT = shellfish
```



Zoo example

```
>>> dt.dt.display()
```

```
Test legs
```

```
legs = 0 ==> Test fins
```

```
  fins = 0 ==> Test toothed
```

```
    toothed = 0 ==> RESULT = shellfish
```

```
    toothed = 1 ==> RESULT = reptile
```

```
  fins = 1 ==> Test milk
```

```
    milk = 0 ==> RESULT = fish
```

```
    milk = 1 ==> RESULT = mammal
```

```
legs = 2 ==> Test hair
```

```
  hair = 0 ==> RESULT = bird
```

```
  hair = 1 ==> RESULT = mammal
```

```
legs = 4 ==> Test hair
```

```
  hair = 0 ==> Test aquatic
```

```
    aquatic = 0 ==> RESULT = reptile
```

```
    aquatic = 1 ==> Test toothed
```

```
      toothed = 0 ==> RESULT = shellfish
```

```
      toothed = 1 ==> RESULT = amphibian
```

```
  hair = 1 ==> RESULT = mammal
```

```
legs = 5 ==> RESULT = shellfish
```

```
legs = 6 ==> Test aquatic
```


```
  aquatic = 0 ==> RESULT = insect
```

```
  aquatic = 1 ==> RESULT = shellfish
```

```
legs = 8 ==> RESULT = shellfish
```

**After adding the
shark example
to the training
data & retraining**

Weka



- Open-source Java machine learning tool
- <http://www.cs.waikato.ac.nz/ml/weka/>
- Implements many classifiers & ML algorithms
- Uses common data representation format; easy to try different ML algorithms and compare results
- Comprehensive set of data pre-processing tools and evaluation methods
- Three modes of operation: GUI, command line, Java API

Weka Explorer

Preprocess Classify Cluster Associate Select attributes Visualize

Classifier

Choose **J48 -C 1.0 -M 0**

Test options

Use training set

Supplied test set

Cross-validation Folds

Percentage split %

(Nom) WillWait

Result list (right-click for options)

20:32:20 - trees.J48
 20:32:38 - trees.J48
 20:32:40 - trees.J48
 20:33:06 - trees.J48
 20:44:28 - trees.J48

Status

OK  x 0

Weka GUI Chooser

Program Visualization Tools Help



Applications

Waikato Environment for Knowledge Analysis
 Version 3.8.0
 (c) 1999 - 2016
 The University of Waikato
 Hamilton, New Zealand

Classifier output

J48 pruned tree

```

-----
HowCrowded = None: No (2.0)
HowCrowded = Some: Yes (4.0)
HowCrowded = Full
|   Hungry = Yes
|   |   IsFridayOrSaturday = Yes
|   |   |   Price = $: Yes (2.0)
|   |   |   Price = $$: Yes (0.0)
|   |   |   Price = $$$: No (1.0)
|   |   IsFridayOrSaturday = No: No (1.0)
|   Hungry = No: No (2.0)
  
```

Number of Leaves : 7

Size of the tree : 11

Time taken to build model: 0.11 seconds

=== Evaluation on training set ===

Common .arff* data format

@relation heart-disease-simplified

Numeric attribute

@attribute age numeric

@attribute sex { female, male }

@attribute chest_pain_type { typ_angina, asympt, non_anginal, atyp_angina }

@attribute cholesterol numeric

@attribute exercise_induced_angina {no, yes}

@attribute class {present, not_present}

Nominal attribute

@data

Training data

63,male,typ_angina,233,no,not_present

67,male,asympt,286,yes,present

67,male,asympt,229,yes,present

38,female,non_anginal,?,no,not_present

...


*ARFF = Attribute-Relation File Format

Weka demo

Install Weka


- Download and install Weka
- cd to your weka directory
- Invoke the GUI interface or call components from the command line
 - You will probably want to set environment variables (e.g., CLASSPATH) or aliases (e.g., weka)

Open Weka app




- `cd /Applications/weka`
`java -jar weka.jar`
- Available apps optimized for different tasks
- Start with Explorer


Explorer Interface



Starts with Data Preprocessing; open file to load data



Load restaurant.arff training data



We can inspect/remove features

Weka Explorer

Preprocess | Classify | Cluster | Associate | Select attributes | Visualize

Open file... | Open URL... | Open DB... | Generate... | Undo | Edit... | Save...

Filter

Choose None [Apply] [Stop]

Current relation

Relation: restaurant Instances: 12 Attributes: 11 Sum of weights: 12

Attributes

All | None | Invert | Pattern

No.	Name
1	<input checked="" type="checkbox"/> AlternateNearby
2	<input type="checkbox"/> HasBar
3	<input type="checkbox"/> IsFridayOrSaturday
4	<input type="checkbox"/> Hungry
5	<input type="checkbox"/> HowCrowded
6	<input type="checkbox"/> Price
7	<input type="checkbox"/> Raining
8	<input type="checkbox"/> Reservations
9	<input type="checkbox"/> Type
10	<input type="checkbox"/> WaitingTime
11	<input type="checkbox"/> WillWait

[Remove]

Selected attribute

Name: AlternateNearby Type: Nominal
Missing: 0 (0%) Distinct: 2 Unique: 0 (0%)


No.	Label	Count	Weight
1	Yes	6	6.0
2	No	6	6.0

Class: WillWait (Nom) [Visualize All]


Status

OK [Log] x 0

Select classify then J48



Adjust parameters & training options; click start to train



See the training results

The screenshot shows the Weka Workbench interface. The 'Classifier' tab is active, and the 'J48 -C 1.0 -M 1' classifier is selected. The 'Test options' section shows 'Cross-validation' selected with 10 folds. The 'Classifier output' pane displays the following results:


```
=== Classifier model (full training set) ===  
J48 pruned tree  
-----  
HowCrowded = None: No (2.0)  
HowCrowded = Some: Yes (4.0)  
HowCrowded = Full  
| Hungry = Yes  
| | IsFridayOrSaturday = Yes  
| | | Price = $: Yes (2.0)  
| | | Price = $$: Yes (0.0)  
| | | Price = $$$: No (1.0)  
| | IsFridayOrSaturday = No: No (1.0)  
| Hungry = No: No (2.0)  
  
Number of Leaves :    7  
Size of the tree :    11  
  
Time taken to build model: 0.05 seconds  
  
=== Stratified cross-validation ===  
=== Summary ===
```

The 'Result list' shows a single entry: '22:23:29 - trees.J48'. The 'Status' bar at the bottom indicates 'OK'.

Compare results

HowCrowded = None: No (2.0)
HowCrowded = Some: Yes (4.0)
HowCrowded = Full
| Hungry = Yes
| | IsFridayOrSaturday = Yes
| | | Price = \$: Yes (2.0)
| | | Price = \$\$: Yes (0.0)
| | | Price = \$\$\$: No (1.0)
| | IsFridayOrSaturday = No: No (1.0)
| Hungry = No: No (2.0)

**J48 pruned tree: nodes:11;
leaves:7, max depth:4**




**ID3 tree: nodes:12; leaves:8,
max depth:4**

scikit-learn



- Popular open source ML and data analysis tools for Python
- Built on [NumPy](#), [SciPy](#), and [matplotlib](#) for efficiency
- However decision tree tools are a weak area
 - E.g., data features must be numeric, so working with restaurant example requires conversion
 - Perhaps because DTs not used for large problems
- We'll look at using it to learn a DT for the classic [iris flower dataset](#)



50 samples from each of three species of Iris (setosa, virginica, versicolor) with four data features length and width of the sepals and petals in centimeters

iris_decision_tree.ipynb - Colab x

https://colab.research...


iris_decision_tree.ipynb

File Edit View Insert Runtime Tools Help

COMMENT SHARE

CODE TEXT CELL CELL RAM Disk EDITING

Decision tree example using the classic IRIS [data set](#), which has 50 samples from each of three species of Iris (setosa, virginica, versicolor). Four features were measured from each sample: the length and width of the sepals and petals in centimeters.



Double-click (or enter) to edit

```
[1] from sklearn import tree
    from sklearn.datasets import load_iris
    import graphviz
```

The `load_iris()` function returns a scikit bunch object, which has a data and target for our iris dataset

The iris data is an 150x4 array and the iris target is a vector of 150 values

```
[2] iris = load_iris()
    print('data:', iris.data.shape, 'target', iris.target.shape)
```


```
>>> data: (150, 4) target (150,)
```

Use scikit's DecisionTreeClassifier and use the fit() method to build a decision tree classifier the data and target

```
[3] clf = tree.DecisionTreeClassifier()
    clf = clf.fit(iris.data, iris.target)
```

We can visualize the decision tree using the `Graphviz` open source graph visualization

Scikit DT



```
from sklearn import tree, datasets
import graphviz, pickle

iris = datasets.load_iris()


clf = tree.DecisionTreeClassifier()
clf = clf.fit(iris.data, iris.target)

pickle.dump(clf, open('iris.p', 'wb'))

tree.export_graphviz(clf, out_file="iris.pdf")
```

<http://bit.ly/iris471>

Weka vs. scikit-learn vs. ...



- Weka: good for experimenting with many ML algorithms
 - Other tools are more efficient & scalable
- [Scikit-learn](#): popular and efficient suite of open-source machine-learning tools in Python
 - Uses NumPy, SciPy, matplotlib for efficiency
 - Preloaded into Google's [Colaboratory](#)
- Custom apps for a specific ML algorithm are often preferred for speed or features